



## WHY BUY THIS TIRE?

Built to withstand heavy loads, this rugged flotation implement tire delivers superior traction and minimizes soil compaction.

- Tubeless high flotation tire delivers superior self-cleaning characteristics
- Suitable for all AG implements, in both drive and free-rolling applications
- Offers high load capacity at low inflation pressures, minimizing soil compaction



PRODUCT CODE	TIRE SIZE	TT/TL/T&F	PLY/LOAD INDEX	SPEED MAX (MPH)	OUTER DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM (INCH)	MAX LOAD/PRESSURE (LB/PSI)
● 1963402522	48X2500-20	TL	12 PLY	30	50.1	24.8	57	20.5HF,20.5VF	7167/45
● 1963403122	48X3100-20	TL	12 PLY	30	50.2	30.5	57	26.00HF,26.00VF	6946/41
● 1963404615	400/60-15.5	TL	14 PLY	20	34.4	15.9	20	13	8115/66
● 1963407522	700/50-22.5	TL	16 PLY	25	50.0	27.6	25	24	(14,771/10,472)/41
● 1963415525	550/60-22.5	TL	16 PLY	25	48.7	21.7	25	16	(12,015/8,267)/44
● 1963415625	500/60-22.5	TL	12 PLY	25	46.1	18.7	25	16	9096/35
● 1963415626	500/60-22.5	TL	16 PLY	25	46.1	18.7	25	16	10750/47
● 1963416525	600/50-22.5	TL	16 PLY	25	46.1	22.7	25	20	(11,354/8,047)/38
● 1963417425	700/40-22.5	TL	16 PLY	25	46.1	26.6	25	24	11687/38
● 1963417426	700/40-22.5	TL	18 PLY	25	46.1	26.6	25	24	(12,346/8,818)/50

● A ● B

